



SMITH ENTERPRISE, INC.

LEADER IN WEAPONS UPGRADES FOR OVER 40 YEARS

1701 West 10th Street, Suite 14, Tempe, Arizona 85281
(480) 964-1818, Fax (480) 921-9987 www.smithenterprise.com

M14 GAS LOCK FRONT SIGHTS (GLFS) Standard issue on USN and USAF MK14 Mod O and M14SE SASS



1) Gas Lock Front –
Hooded (GLFS-H),
P/N 2012

2) GLFS-D-18,
P/N 2013

3) GLFS-D-22,
P/N 2011

Developed to meet a US Navy requirement and now standard issue, the patent pending Gas Lock Front Sight (GLFS) is intended to enable the user of the M-14 to effectively mount a sound suppressor on the Vortex DC flash suppressor.

The GLFS comes in three configurations, the GLFS-Hooded (Left), which was first adopted by the US Army Second Infantry Division on their M14SE “Crazy Horse” SASS and on US Navy full-length M14SEs. The GLFS-D-22 allows the use of a traditional M14 dovetail sight and is intended for use on 22.0” (i.e. standard length) barrels. The GLFS-D-18 is intended for use on 18.0” barrels and is current issue on the USN MK 14 Mod 0, Mod 1, and Mod 2 rifles. This design will also be incorporated into the forthcoming USAF MK14 rifle. GLFS units are chrome moly steel, heat treated and Melonited.

The GLFS-D models will also accept the our SEI Tritium front sight. Contact SEI for details on availability.

NOTE: Now available for civilian sales.

Part Number	Description
2011	GLFS-D-22 (Dovetail), for 22” bbls
2012	GLFS-H (Hooded), for 18” and 22” bbls (US Army)
2013	GLFS-D-18 (Dovetail), for 18” bbls (USN & USAF)

(Information current as of 15 November 11)